Residential / Commercial


N-Type

MONO-FACIAL MODULE

Type: DMXXXM10T-66HSW/HBW

Power Range: 520- 535 W

Max. Efficiency: 22.53 %



Better Performance

Our modules perform better on sunny and hot days thanks to its optimized temperature coefficient.

Excellent Low Light Performance

Our modules can also provide higher power output under low light conditions, such as sunset, cloudy, or dawn.

Excellent Quality

More than 40 years' experience of manufacturing and intensive quality tests above the IEC standard ensures reliable modules and a secured investment.

Assumption of Environmental, Social and Governance Responsibility (ESG)

DMEGC stands for his responsibility. Production is certified according to SA 8000 (ILO standards).

High-quality service

We provide a customer-oriented and localized services, covering pre-sale, sale and after-sales.

Certifications

SA 8000	ILO Standards. Social responsibility standards
ISO 9001	Quality management system
ISO 14001	Environmental management system
ISO 45001	Occupational health and safety management system
ISO 50001	Energy management system


DE 50188598

A member of Hengdian Group

DMXXXM10T-66HSW/HBW

Module Specification

Cell Type	N -type Mono-crystalline , 132 (6x22)
Dimensions (mm)	2094 x 1134 x 35
Weight (kg)	26
Front Cover	3.2 mm tempered solar glass with anti -reflective coating
Rear Cover	Backsheet
Junction Box	3 Diodes, IP68 according to IEC 62790
Cables	4 mm² solar cable, 1.3 m or Customized Length
Connector Type	PV-ZH202B or MC4 (1000V) PV-ZH202B or MC4-EVO 2A (1500V)



Electrical Specifications[1]

Module Type	DM520M10T-66HSW/HBW DM520M10T-66HSW/HBW-V		DM525M10T-66HSW/HBW DM525M10T-66HSW/HBW-V		DM530M10T-66HSW/HBW DM530M10T-66HSW/HBW-V		DM535M10T-66HSW/HBW DM535M10T-66HSW/HBW-V	
Testing Condition	STC[2]	NMOT[3]	STC	NMOT	STC	NMOT	STC	NMOT
Maximum Power (Pmax/W)	**520**	391	**525**	395	**530**	399	**535**	402
Maximum Power Current (Imp/A)	13.20	10.58	13.26	10.63	13.32	10.68	13.38	10.73
Maximum Power Voltage (Vmp/V)	39.43	36.97	39.62	37.15	39.81	37.32	40.00	37.50
Short-circuit Current (Isc/A)	13.84	11.17	13.89	11.21	13.94	11.25	13.99	11.29
Open-circuit Voltage (Voc/V)	47.29	44.92	47.48	45.10	47.67	45.28	47.86	45.46
Module Efficiency STC (%)	**21.90**		**22.11**		**22.32**		**22.53**	

[1] Measurements according to IEC 60904-3, Measurement tolerance: ISC / VOC: ±3 %,
[2] STC (Standard Test Condition): Radiation 1000 W/m², Module temperature 25℃, AM = 1.5
[3] NMOT: Radiation 800 W/m², Ambient temperature 20℃, AM = 1.5, Wind Speed 1 m/s

Certifications and Warranty

Certifications	IEC 61215, IEC 61730
	Ammonia Corrosion Test: IEC 62716
	Salt Mist Corrosion Test: IEC 61701
	PID (IEC TS 62804); LeTID (IEC TS 63342)
	Dust & Sand (IEC 60068)
WEEE Registration No.	DE 50188598
Product Warranty	20 years
Peak Power Warranty	30 years linear warranty

1.) First year: min. 99 %. 2.) From the 2nd year: Max. 0.4 % degradation annually. 3.) Min. 87.4 % in the 30th year.

Operating conditions

Operating Temperature (℃)	-40 to +85
Maximum System Voltage(V)	1000V/1500V DC (IEC)
Overcurrent protection rating (A)	25
Power Performance Tolerance (%)	0 / +3
Protection class	II
Max. Test Load, Push/Pull (Pa)	Snow 5400 / Wind 2400
Max. Design Load, Push/Pull (Pa)	3600 / 1600
Fire Rating Class	IEC Class C


Temperature Characteristics

Nominal Module Operating Temperature (NMOT)	45 ± 2 ℃
Temperature Coefficient of Pmax (%/℃)	-0.31
Temperature Coefficient of Voc (%/℃)	-0.25
Temperature Coefficient of Isc (%/℃)	+0.060

Packaging

Container	40' HQ
Pallet Dimensions(mm)	2145 × 1140 × 1250
Pieces per Pallet	31
Pieces per Container	682

Current–Voltage Curve (535 W)



Statement: The installation instructions and the warranty conditions must be followed. Due to technological progress, product parameters will be adjusted accordingly.When signing the contract, the latest data of the company shall prevail.

Hengdian Group DMEGC Magnetics Co.,Ltd.
Hengdian Industrial Zone, Dongyang City Zhejiang Province, China 322118
Tel: 0086-579-8658-8825 Fax: 0086-579-8655-4845
E-mail: solar@dmegc.com.cn, Website: www.dmegcsolar.com

All information in this data sheet corresponds to EN 50380.Changes and errors excepted.
Status: 06/2023, Document: **EN_DS-M10T-66HSW/HBW-202306_1**

Copyright © 2023 Hengdian Group DMEGC Magnetics. All rights reserved.