luxra® PURE ENERGY



LOW REFLECTION

Suitable for applications with severe Glare requirements (e.g. next to roads or airports and residential complexes).

HIGHEST PERFORMANCE

Excellent N-type TOPCon bifacial cell efficiency for output up to maximum performance of 450 Wp available.

LIGHT WEIGHT

Low module weight with double glass for maximum high static load on front side and high hail resistance.

DESIGN AND SECURITY

Elegant black framework and all black design, together with double glass for technical security. Reliable for your free clean energy.

RESIDENTIAL NEW GENERATION HIGH POWER

LUXRA® PURE MODULE LX-450N

THE POWERFUL AND RELIABLE SOLAR MODULE FOR MULTI-APPLICATION SOLUTIONS

SOLARIF CERTIFIED

Inherent defect coverage for certified panels with inline-quality inspection

30 YEARS GUARANTEED

Performance Guarantee 30 years linear power output warranty

30 YEARS WARRANTY

Product Warranty 30 years limited warranty on product quality


SWISS BRAND

WWW.LUXRA.CH

LUXRA® PURE LX-450N-54HC-BFGG (TOPCON) TECHNICAL DATA

RESIDENTIAL - NEW GENERATION HIGH POWER

22.5%	0-3%	<2%	0.4%	INNOVATION SMBB & HALF CUT CELLS
MODULE EFFICIENCY	POWER TOLERANCE	FIRST YEAR POWER DEGRADATION	YEAR 2-30 POWER DEGRADATION	LOWER OPERATION TEMPERATURE



ELECTRICAL DATA AT STC*

Peak Power (Pmax)	(W)	450
Maximum Power Voltage (Vmp)	(V)	33,07
Maximum Power Current (Imp)	(A)	13,61
Open-circuit Voltage (Voc)	(V)	39,73
Short-circuit Current (Isc)	(A)	14,22
Module Efficiency	(%)	22,54
Operating Temperature		- 40° ~ + 85° C
Maximum System Voltage		1500V
Maximum Series Fuse Rating		25A
Power Tolerance		0~+3%
Mechanical Test Load		Front - 5400Pa - Rear - 2400Pa

*STC (Standard Test Condition): Irradiance 1000W/ m2, Module Temperature 25° C, AM 1.5

ELECTRICAL DATA AT NMOT*

Peak Power (Pmax)	(W)	339
Maximum Power Voltage (Vmp)	(V)	30,82
Maximum Power Current (Imp)	(A)	11
Open-circuit Voltage (Voc)	(V)	37,64
Short-circuit Current (Isc)	(A)	11,48

*NMOT (Under Nominal Module Operating Temperature), Irradiance of 800W/ m2, Spectrum AM 1.5, Ambient Temperature 20°, Wind Speed 1m/s

TEMPERATURE CHARACTERISTICS

Temperature coefficient of Pmax	- 0,29%/k
Temperature coefficient of Voc	- 0,25%/k
Temperature coefficient of Isc	0,04%/k
NMOT	43 ± 2° C

MECHANICAL DATA

Cell Type	Mono-Crystalline N-TYPE TOPCon
Cell Arrangement	108pcs (2(6x9))
Dimensions (LxWxH)	1762 x 1134 x 30 mm 1,99 m²
Weight	22,5 kg
Front Cover	1.6 mm high transmittance, AR coated tempered glass
Back Cover	1.6 mm high transmittance, heat strengthened glass
Frame	Black coated Aluminium Alloy
Junction Box	IP68, 3 Bypass Diodes
Cable Type	4mm²
Length of Cable	1000 mm
Connector	Compatible with MC4 PV Connector

PACKAGING


Packing Type	40 ft HQ
Piece/ Pallet	36
Piece/ Container	936

WARRANTY


Product Material & Workmanship	30 years
Linear Performance Warranty	30 years

IV Curves for Front-Side Illumination of 450 Wp Panel


CURRENT - VOLTAGE CURVE UNDER DIFFERENT IRRADIANCE



CURRENT - VOLTAGE CURVE UNDER DIFFERENT WORKING TEMPERATURES



LINEAR PERFORMANCE WARRANTY



The information contained in these specifications is subject to change without prior notice.
Luxra International B.V. reserves the exclusive right to final interpretation of all content.

Email us: info@luxra.ch
Contact us: +41 41 5331195
Holding: Riedstrasse 7, CH - 6330 Cham, Switzerland
Sales: Schoterlandseweg 45, NL - 8451 KA Oudeschoot, The Netherlands
WWW.LUXRA.CH