ZXM6-HLD120 **Series**


Znshinesolar 5BB HALF-CELL **BLACK** Light-Weight Double Glass Mono PV Module

ZNSHINESOLAR

120

Mono Poly Solutions

310W | 315W | 320W | 325W | 330W | 335W




Made with selected materials and components to grant quality, duration, efficiency and through outputs, the ZXM6-HLD120 double glass modules by ZNSHINE SOLAR feature have both decorative and shading functions.They represent the perfect choice for BIPV and BAPV construction applications. This allows you to produce clean energy while reducing your energy bill.

ZNSHINE SOLAR' S ZXM6-HLD120 double glass solar modules are tested and approved by international acknowledged laboratories, so that we can offer our customers a reliable and price-quality optimized product.

12 years product warranty/30 years output warranty

0.5% Annual Degradation over 30 years



Half Cell Technology

5BB

Module RS decreases, FF (fill factor) increases, power gain is stable above 2%, and can be increased by 5~10W

High Efficiency

Graphene coating can increase about 2W of the module efficiency by rising around 0.5% of the light transmission

Anti PID

PID

Limited power degradation of ZXM6-HLD120 module caused by PID effect is guaranteed under strict testing condition for mass production

Better Weak Illumination Response

Lower temperature coefficient and wide spectral response, higher power output, even under low-light settings

Easy to install

The module is very light in weight so the installation is easier and transport costs are lower

Customerization——Grahpene Coating

Graphene coating modules can increase power generation and self-cleaning, also can save maintainance cost

ZNShine PV-Tech Co., LTD, founded in 1988, is a world-leading high-performance PV module manufacturer, PV power station developer, EPC and power station operator. With its state-of-the-art production lines, the company boasts module output of 5GW. Bloomberg has listed ZNShine as a global Tier 1 PV manufacturer and Top 4 reliable PV supplier.

www.znshinesolar.com

ZXM6-HLD120 **Series** | Znshinesolar 5BB HALF-CELL **BLACK** Light-Weight Double Glass Mono PV Module

ZNSHINESOLAR

ELECTRICAL PROPERTIES | STC*

Module Type	ZXM6-HLD120 -310/M	ZXM6-HLD120 -315/M	ZXM6-HLD120 -320/M	ZXM6-HLD120 -325/M	ZXM6-HLD120 -330/M	ZXM6-HLD120 -335/M
Nominal Power Watt Pmax(W)	310	315	320	325	330	335
Power Output Tolerance Pmax(%)	0~+3	0~+3	0~+3	0~+3	0~+3	0~+3
Maximum Power Voltage Vmp(V)	33.1	33.3	33.5	33.7	33.9	34.1
Maximum Power Current Imp(A)	9.38	9.47	9.57	9.65	9.74	9.83
Open Circuit Voltage Voc(V)	39.8	40.0	40.2	40.4	40.6	40.8
Short Circuit Current Isc(A)	9.99	10.05	10.12	10.18	10.24	10.30
Module Efficiency (%)	18.24	18.54	18.83	19.12	19.42	19.71

*STC (Standard Test Condition): Irradiance 1000W/m², Module Temperature 25℃, AM 1.5
*The data above is for reference only and the actual data is in accordance with the pratical testing

ELECTRICAL PROPETIES | NMOT*

Maximum Power Pmax(Wp)	230.0	233.4	237.4	240.7	243.9	247.6
Maximum Power Voltage Vmpp(V)	30.4	30.6	30.9	31.1	31.3	31.6
Maximum Power Current Impp(A)	7.57	7.62	7.69	7.74	7.79	7.84
Open Circuit Voltage Voc(V)	36.9	37.1	37.3	37.5	37.6	37.8
Short Circuit Current Isc(A)	8.08	8.12	8.18	8.23	8.28	8.32

*NMOT(Nominal module operating temperature):Irradiance 800W/m²,Ambient Temperature 20℃,AM 1.5,Wind Speed 1m/s
*The data above is for reference only and the actual data is in accordance with the pratical testing

TEMPERATURE RATINGS

NMOT	45℃ ±2℃
Temperature coefficient of Pmax	-0.37%/℃
Temperature coefficient of Voc	-0.29%/℃
Temperature coefficient of Isc	0.05%/℃

*Do not connect Fuse in Combiner Box with two or more strings in parallel connection

WORKING CONDITIONS

Maximum system voltage	1500 V DC
Operating temperature	-40℃~+85℃
Maximum series fuse	20 A
Maximum load(snow/wind)	5400 Pa / 2400 Pa


MECHANICAL DATA

Solar cells	Mono 158.75*79.375mm
Cells orientation	120 (6×20)
Module dimension	1696×1002×25mm(With Frame)
Weight	22 kg
Glass	2.0mm+2.0mm heat strengthened glass
Junction box	IP 68，3 diodes
Cables	4 mm² ,350 mm
Connectors	MC4-compatible


PACKAGING INFORMATION

Packing Type	40′ HQ
Piece/Box	42
Piece/Container	1092/1144

DIMENSION OF THE PV MODULE (mm)



I-V CURVES OF THE PV MODULE



Add : 1#, Zhixi Industrial Zone, JintanJiangsu 213251, P.R. China
Tel: +86 519 6822 0233 E-mail: info@znshinesolar.com

Remark: please read safety and installation instructions before using the product | Subject to change without prior notice © ZNSHINE SOLAR 2020 | Version: ZXM6-HLD120 2002.E