ZT Series Monocrystalline

Solar Module

240S/245S

ZYTECH SOLAR

Efficiency

High Module Conversion Efficiencies utilizing three buss bars per cell

Warranty

Peace of Mind Guaranteed with a twenty-five Year Linear Power Warranty and Product Quality Ensured for ten years

Certifications

IEC 61215:2005, IEC 61730:2004, UL 1703-3rd Ed: 2014, ULC/ORD C1703-01:2014, ISO 9001:2008, PSK 024:2008


Tolerance

Strict quality control guarantees higher average power output according to tolerance -3% to +3%

Optimized Strength

Minimum standard for wind 2700Pa to a Mechanical load capacity up to 5400Pa meet customer's needs for durability on high mountains, sea shores, & paths between buildings





EMPOWERING You

To Change The Future

Zytech was founded in Zaragoza (Spain) in 2005. Since then the group has progressively increased its infrastructure and production capacity to become a global power with offices and headquarters in Spain, Germany, France, Italy, BENELUX, Mexico, United States of America, Korea, Malaysia and China.

Zytech takes pride in their R&D department which specializes in product enhancement, state-of-the-art machinery and rigorous quality control that guarantees an European quality product at the best price.

www.zytechsolar.com

ZT Series Monocrystalline

Solar Module

240S/245S

ZYTECH SOLAR


Cell Data	
Technology	Monocrystalline Silicon
Number Per Module	60
Dimension	156 x156 mm
Orientation	6 × 10

Thermal Data	
Nominal Operating Cell Temperature（NOCT）	45°C ± 2°C
Temperature Coefficient of Voc	-0.34% / °C
Temperature Coefficient of Isc	+0.037 % / °C
Temperature Coefficient of Power Pmax	- 0.48 % / °C


Electrical Data（STC）		ZT 240S	ZT 245S
Maximum power（W）	Pmax	240	245
Power Output Tolerance（%）		-3 to 3%	
Maximum Power Voltage（V）	Vmpp	30.56	30.76
Maximum Power Current（A）	Impp	7.85	7.96
Open Circuit Voltage（V）	Voc	37.49	37.74
Short Circuit Current（A）	Isc	8.54	8.58
Module Efficiency（%）		17.20%	17.60%

* At Standard Conditions（STC） Irradiance 1000 watt/m², spectrum AM 1,5 at a cell temperature of 25°C

System Integrated Parameters	
Maximum System Voltage SCII	1000 VDC（UL1000V）
Maximum Reverse Current	Do not apply external voltages larger than Voc to the module
Operating Temperature	-40~+85°C
Max Series Fuse Rating	15A



IU and PU Curve



Physical Characteristics	
Module Dimension（L×W×H）	1640x992x35/40 mm Code: PV30034 - ZT245S
Weight	18 kg
J-Box	IP65 or IP67 rated, 3/6 diodes
Connector	MC4 or MC4 Compatible
Glass	3.2mm（0.13 in）, High Transmission, AR Coated Tempered Glass
Cable	4 mm² PV cable, 1000mm/1200mm
Frame	Silver Anodized Aluminum Alloy

Packing Configuration	
Modules Per Pallet	26
Pallet Per 40 'HQ Container	22（572 pcs）
Packing Box Dimension（L×W×H）	2000×1150×1040 mm
Packing Orientation	Side

ZYTECH SOLAR S.L.

P. Industrial Centrovía- C/R. Janeiro, 12
50198 La Muela (Zaragoza) SPAIN
Tel: +34 976 141819 / Fax: +34 976+141818
info@zytech.es
www.zytechsolar.es

Zytech Solar reserves the right to change specifications without notice